

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) An office chair mounted on a movable base having an armrest that can be raised and lowered comprising:

- (a) said office chair having a back;
- (b) a bracket mounted on the back of said office chair at least about six inches above the plane of the top of the seat of said office chair, said bracket having a cavity;
- (c) an armrest support having a first portion rotatably mounted within said bracket cavity and a second portion extending from said bracket to a position selected from the group consisting of the right and the left of a user wherein said user is positioned on the seat of said office chair and is facing away from the back of the chair;
- (d) an armrest body mounted on the end of said armrest support distal to said bracket;
- (e) a rotation lock which, when engaged, prevents said armrest support from rotating within said bracket, said rotation lock mounted in said bracket; and
- (f) a rotation lock release member having a switch positioned on said armrest support near said armrest body.

2. (canceled)

3. (canceled)

4. (previously presented) A chair with an adjustable arm comprising:

- (a) a support for a back of said chair connected to a base of said chair;
- (b) a bracket mounted on said back support;
- (c) a first link pivotally mounted to said bracket mounted on said back support;
- (d) a second link pivotally mounted to said bracket mounted on said back support;
- (e) a second bracket pivotally mounted to the ends of said first and said second links at the end of each link distal to the bracket mounted on said back support; and
- (f) an armrest body mounted to said second bracket.

5. (previously presented) The chair with an adjustable arm of claim 4 further comprising a locking mechanism at the interface between (a) one of said links mounted to the bracket mounted on said back support and (b) said second bracket.

6. (previously presented) The chair with an adjustable arm of claim 4 further comprising

- (a) a third bracket mounted on said back support;
- (b) a third link pivotally mounted to said third bracket;
- (c) a fourth link pivotally mounted to said third bracket;

- (d) a fourth bracket pivotally mounted to the ends of said third and said fourth links at the end of each link distal to the third bracket; and
- (e) a second armrest body mounted to said fourth bracket.

7. (previously presented) The chair with an adjustable arm of claim 4 further comprising a slider-crank joint at the interface between one link and one bracket.

8.-10. (canceled)

11. (previously presented) The chair with an adjustable arm of claim 4 further comprising said bracket mounted on said back support being at least about 6 inches above a rear portion of the seat of said chair.

12.-21. (canceled)

22. (currently amended) In a chair comprising a back support, an adjustable armrest mechanism mounted to the back support, the adjustable armrest mechanism comprising:

- (a) an armrest;

- (b) at least two substantially parallel bars, each parallel bar comprising a first end and a second end, the first end pivotably mounted to the armrest, and at least one second end movably engaged with the back support; and
- (c) ~~The adjustable armrest mechanism of claim 20 wherein the positioning means~~ comprises a first ratchet surface mounted to an interior wall of the back support and a locking bar mounted to the second end, wherein the locking bar comprises a second ratchet surface complementary to the first ratchet surface[[]], wherein the first ratchet surface, second ratchet surface and locking bar cooperate with the second end and the back support to movably engage the second end with the back support.

23. (currently amended) The adjustable armrest mechanism of claim 22 wherein the locking bar further comprises a spring engaged with a piston, the piston engaged with the interior wall of the back support to bias the ~~positioning means~~ first ratchet surface toward engagement ~~of the second end and the back support~~ with the second ratchet surface.

24. (canceled)

25. (currently amended) The adjustable armrest mechanism of claim ~~24~~ 23 ~~wherein the positioning means further comprises~~ comprising at least two first ratchet surfaces mounted on opposite sides of an interior of the back support, and at least two locking bars mounted to the second

Application Ser. No. 10/693,154
Amendment dated August 14, 2008
Reply to Advisory Action of July 29, 2008

ends, wherein the at least two locking bars comprise at least two second ratchet surfaces complementary to the first ratchet surfaces.

26.-33. (canceled)